

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 541 140 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 92202905.3

(51) Int. Cl.⁵: H02H 3/00

(22) Date of filing: 22.09.92

(30) Priority: 21.10.91 US 779766

(43) Date of publication of application:
12.05.93 Bulletin 93/19

(84) Designated Contracting States:
DE FR GB IT

(68) Date of deferred publication of the search report:
30.03.94 Bulletin 94/13

(71) Applicant: GENERAL MOTORS CORPORATION
General Motors Building

3044 West Grand Boulevard
Detroit Michigan 48202(US)

(72) Inventor: Schnelder, Eric Duane
506 Stonehedge Drive
Carmel, Indiana 46032(US)

(74) Representative: Denton, Michael John et al
Patent Section
1st Floor
Gideon House
28 Chapel Street
Luton Bedfordshire LU1 2SE (GB)

(54) Drive apparatus for a power device.

(57) A drive apparatus (10) which electrically isolates logic level and high-side circuits and detects high side power device fault conditions at the isolated, logic level side of the circuit. When an overvoltage or overcurrent condition occurs at the power semiconductor device (12), a protection circuit (22) disables the conduction of current through the current carrying terminals of the power device, preventing

damage from occurring to the device. Activation of the protection circuit effects an increased current flow in the secondary and primary coils of the isolation transformer (16) between the low side and high side elements. Voltage at the primary coil of the isolation transformer is monitored by low level circuitry (24) to detect the rise in current, indicating a fault to the system controller upon detection.




FIG. 1

BEST AVAILABLE COPY

EP 0 541 140 A3



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 541 140 A2

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 92202905.3

(51) Int. Cl.⁵: H02H 3/00

(22) Date of filing: 22.09.92

(30) Priority: 21.10.91 US 779766

Detroit Michigan 48202(US)

(43) Date of publication of application:
12.05.93 Bulletin 93/19

(72) Inventor: Schnelder, Eric Duane
506 Stonehedge Drive
Carmel, Indiana 46032(US)

(84) Designated Contracting States:
DE FR GB IT

(71) Applicant: GENERAL MOTORS CORPORATION
General Motors Building 3044 West Grand
Boulevard

(74) Representative: Denton, Michael John et al
Patent Section 1st Floor Gideon House 28
Chapel Street
Luton Bedfordshire LU1 2SE (GB)

(54) Drive apparatus for a power device.

(57) A drive apparatus (10) which electrically isolates logic level and high-side circuits and detects high side power device fault conditions at the isolated, logic level side of the circuit. When an overvoltage or overcurrent condition occurs at the power semiconductor device (12), a protection circuit (22) disables the conduction of current through the current carrying terminals of the power device, preventing

damage from occurring to the device. Activation of the protection circuit effects an increased current flow in the secondary and primary coils of the isolation transformer (16) between the low side and high side elements. Voltage at the primary coil of the isolation transformer is monitored by low level circuitry (24) to detect the rise in current, indicating a fault to the system controller upon detection.




FIG. 1

EP 0 541 140 A2